

Z100-M635.03 S11

Manual taper change

Item no. **10206004-01**

HF-Spindle for high-speed milling, -grinding, -drilling, -engraving

Bearings

| | |
|---------------------------|------------------|
| Hybrid ball bearing (pcs) | 4 |
| Lifetime lubricated | maintenance free |

Motor

| | |
|--|---|
| Motor technology | 3-phase asynchronous drive (no brushes or sensors) |
| Frequency | 1.167 Hz |
| Motor poles (pairs) | 2 |
| Rated rotation speed | 35.000 rpm |
| Acceleration/braking value Per second | 10 000 rpm (other values by consultation) |


Power values

Liquid cooled


| | Pmax./5s | S6-60% | S1-100% | |
|-------------|----------|--------|---------|------|
| Rated power | 16,1 | 11,5 | 10 | [kW] |
| Torque | 6,85 | 5,19 | 4,7 | [Nm] |
| Voltage | 380 | 380 | 380 | [V] |
| Current | 38,4 | 28,5 | 25,7 | [A] |

Z100-M635.03 S11

Manual taper change
Item no. **10206004-01**



Dimensions



Performance Diagram
Liquid cooled

Measurement of power is funded by in-house testing.

Characteristics

| | |
|---|--|
| Speed sensor | Differential magneto resistor (TTL) Number of signals = 6 |
| Motor protection | PTC 130°C |
| Housing | Stainless steel |
| Housing diameter | 100 / 80 mm |
| Cooling | Liquid cooled |
| Ambient temperature | + 10°C ... + 45°C |
| Sealing air | |
| Protection category (sealing air turned on) | IP54 |
| Tool change | Manual taper change |
| Tool Holder | HSK-C 40 |
| Clamping range up to | 16 mm |
| Clockwise and anticlockwise | |
| Coupler plug | 5-pin (ECTA 133) motor phases 12-pin (ECTA 133) sensors |
| Weight | ~ 12,5 kg |
| Inner taper run out | < 1 μ |
| Axial run-out | < 1 μ |